

Model	LS-250P	LS-280P	LS-350P
Pressure (MPa)	18	18	18
Production Capacity (ton/hr)	~8-10	~10-12	~18-20
Bale Size (mm)	L1524*W900*H800	L1524*W1000*H1050	L1524*W1000*H1050
Input Size (mm)	L2300*W1474*H762	L2300*W1474*H1012	L2300*W1474*H1012
Interior Size(mm)	L2300*W1524*H762	L2300*W1524*H1012	L2300*W1524*H1012
Bale Weight (kg)	~700	~950	~1000
Main Motor (kW)	45 (x3) 5.5 (x1)	45 (x3) 5.5 (x1)	45 (x4) 5.5 (x1)
No. of Binding Wire (pair)	Adjustable	Adjustable	Adjustable
Machine Size (w/ conveyor)	L15672*W10254*H4200	L15984*W10354*H4200	L15984*W10354*H4200
Machine Weight (ton)	~49	~52	~58
Bale Density (kg/m3)	500-550	450-500	550-600

Conveyor Specification			
Size (mm)	L13006*W1956	L13006*W1956	L13006*W1956
Conveyor Motor (kW)	7.5	7.5	7.5
Motor Speed Reducer	MHF107-15HP-1/50	MHF107-15HP-1/50	MHF107-15HP-1/50
CNVR.Inside Width (mm)	1730	1730	1730
Chain Size (inch)	6	6	6