

Model	LS-60SE	LS-100SE	LS-150SE	LS-200SE	LS-250SE
Pressure (MPa)	18	18	18	18	18
Production Capacity (ton/hr)	~2-3	~3-4	~4-6	~6 - 8	~6 - 8
Bale Size (mm)	L(0-1350)*800*H900	L (0-1450) *W1100*H800	L (0-1600) *W1100*H1250	L(0-1800)*W1100*H1250	L(0-2000)*W1100*H1250
Input Size (mm)	L1350*W750*H900	L1450*W1050*H800	L1740*W1050*H1250	L1740*W1050*H1250	L1740*W1050*H1250
Interior Size(mm)	L1350*W800*H900	L1450*W1100*H800	L1740*W1100*H1250	L1740*W1100*H1250	L1740*W1100*H1250
Bale Weight (kg)	~300(OCC) , ~150(Plastic)	~450(OCC) , ~250(Plastic)	~900-1100(OCC), ~650-850(Plastic)	1100-1200(OCC), ~850-900(Plastic)	1200-1400(OCC), ~900-100(Plastic)
Main Motor (kW)	15	22	37	45	45 (x2)
No. of Binding Wire (pair)	4	3	5	5	5
Machine Size (w/o conveyer)	L6465*W1584*H2400	L7309*W1884*H2400	L8200*W1912*H2500	L8750*W1912*H2500	L9340*W1936*H2600
Machine Weight (ton)	~ 8	~ 12	~ 18	~ 20	~ 23
Bale Density (kg/m3)	330(OCC) , 230(Plastic)	380(OCC), 280(Plastic)	500(OCC), 400(Plastic)	550(OCC), 450(Plastic)	600(OCC), 500(Plastic)