

Model	LS-30ALL	LS-50ALL	LS-60ALL	LS-80ALL	LS-100ALL	LS-150ALL
Pressure (MPa)	16	16	16	16	16	16
Production Capacity (ton/hr)	~1000-1500	~1500-2000	~2000-2500	~3000-3500	~3500-4000	~4000-4500
Bale Size (mm)	L889*W610*H(400-1000)	L889*W610*H(400-1000)	L889*W610*H(400-1000)	L1000*W750*H(500-1100)	L1100*W750*H(500-1100)	L1100*W750*H(500-1100)
Input Size (mm)	L889*H496	L889*H496	L889*H505	L1100*H600	L1100*H600	L1100*H600
Interior Size(mm)	L889*W610*H1446	L889*W610*H1446	L889*W610*H1555	L1118*W737*H1600	L1118*W737*H1735	L1118*W737*H1726
Bale Weight (kg)	~150-250	~200-300	~250-350	~350-450	~450-550	~600-800
Main Motor (kW)	7.5	11	15	18.5	18.5	22
No. of Binding Wire (pair)	4x2	4x2	4x2	5x3	5x3	5x3
Machine Size (mm)	L1175*W865*H3172	L1275*W940*H3200	L1283*W1052*H3308	L1536*W1189*H3541	L1599*W1245*H4022	L1612*W1300*H3987
Machine Weight (ton)	~2	~2.5	~3	~5	~6	~8
Bale Density (kg/m ³)	~400	~450	~500	~650	~750	~900